

# tellus m Union Square





pureWhite

TECHNICAL DATASHEET

# tellus m Union Square

## pureWhite

### Technical Data

Dimensions	115 mm (4.53 in) x 100 mm (3.94 in) [W x H] Length: 654 mm (25.75 in)
Fixture Typ	 pureWhite
Color Temperatures pureWhite	2700 K
Beam Angles	10°
Luminous Flux	3000 lm
Light Source	8 LED(s)
Antiglare	Honeycomb grid, 3mm
LED-Binning	
MacAdam Ellipses Binning	3
Dimming	Non-dimmable
Input Voltage	Power supply: internal   100 - 240, 277 VAC (50 - 60 Hz)   127 - 431 VDC
Power Consumption	Max. 50 W
Power Factor Correction	>= 0.9
Operating Temperature Range	-20 °C / +40 °C -4 °F / +104 °F
Lumen Maintenance [L70]	65'000 h @ 25 °C (77 °F) 40'000 h @ 50 °C (122 °F)
LED-Class	Class 2 LED product
Housing	Extruded aluminium profile Color: black Coating: anodized
Frame	Stainless steel
Load	250 kg 551 lbs
Ingress Protection	IP67
Environment	 outdoor
Certification	





Lindberghstrasse 15  
86343 Koenigsbrunn  
Tel: +49 (0)8231/95787-0  
Fax: +49 (0)8231/95787-29  
[www.biontechnologies.com](http://www.biontechnologies.com)  
[info@biontechnologies.com](mailto:info@biontechnologies.com)

YouTube: <http://www.youtube.com/user/BIONTECHNOLOGIES>

© 2016, BION TECHNOLOGIS GMBH  
All rights reserved / Subject to change / Specifications may change without notice