




cambium xl

TECHNICAL DATASHEET

cambium xl

Technical Data

| | |
|------------------------|--|
| Dimensions | 106 mm x 146 mm x 11 mm 4.17 in x 5.75 in x 0.43 in |
| Control | DMX Output: 2 x DMX 512 (1024 DMX Channels) Input: 8 potential-free inputs binary configurable (255 Trigger) |
| Input Voltage | Power supply: external 5 - 6 VDC |
| Operating Temperature | 0 °C / +50 °C 32 °F - 122°F |
| Housing | Glass-Touch Panel with color display, for standard two gang back box |
| Housing Color(s) | Glass: White Frame: Plastic, black |
| Weight | 0,25 kg (0.55 lbs) |
| Ingress Protection | IP20 |
| Certification |  |
| Additional Information | Remote Control Apps for iOS Android <ul style="list-style-type: none">▪ Direct Color Control (also for White Channel)▪ Life Control for Color Palette, Speed and Dimming▪ Up to 500 scenes can be stored▪ Up to 10 different zones can be controlled simultaneously▪ Clock and Calendar Controller with up to 100 records integrated▪ Network- / USB-Interface▪ RS232 and http Trigger Memory card: MicroSD Card |



Lindberghstrasse 15
86343 Koenigsbrunn
Tel: +49 (0)8231/95787-0
Fax: +49 (0)8231/95787-29
www.biontechnologies.com
info@biontechnologies.com

YouTube: <http://www.youtube.com/user/BIONTECHNOLOGIES>

© 2023, BION TECHNOLOGIS GMBH
All rights reserved / Subject to change / Specifications may change without notice