



linea m hp indoor

pureWhite | pureColor

SPECIFICATION SHEET

BION TECHNOLOGIES GMBH

Lindberghstrasse 15
86343 Koenigsbrunn

Tel: +49 (0)8231/95787-0
Fax: +49 (0)8231/95787-29

www.biontechnologies.com
info@biontechnologies.com

YouTube: <http://www.youtube.com/BIONTECHNOLOGIES>

© 2016, BION TECHNOLOGIS GMBH
All rights reserved / Subject to change / Specifications may change without notice.

Project	Fixture#	Date
		Firm

Ordering Information

Choose the option that suits your needs and write its corresponding code on the appropriate line to form the product code.

LIN-M-HP-IN- _____ - _____ - _____ - _____ - _____ - _____ - Y03

TYP - LUMINOUS COLOR	BEAM ANGLE	HOUSING COLOR	LEADERCABLE LENGTH	GLARE PROTECTION	MOUNTING OPTION																									
<table style="width: 100%; border-collapse: collapse;"> <tr><th colspan="2" style="text-align: left; padding: 2px;">TYP - LUMINOUS COLOR</th></tr> <tr><td style="padding: 2px;">PW22 pureWhite - 2200 K</td></tr> <tr><td style="padding: 2px;">PW27 pureWhite - 2700 K</td></tr> <tr><td style="padding: 2px;">PW30 pureWhite - 3000 K</td></tr> <tr><td style="padding: 2px;">PW40 pureWhite - 4000 K</td></tr> </table>	TYP - LUMINOUS COLOR		PW22 pureWhite - 2200 K	PW27 pureWhite - 2700 K	PW30 pureWhite - 3000 K	PW40 pureWhite - 4000 K	<table style="width: 100%; border-collapse: collapse;"> <tr><th colspan="2" style="text-align: left; padding: 2px;">HOUSING COLOR</th></tr> <tr><td style="padding: 2px;">AA Aluminium anodized (Standard)</td></tr> <tr><td style="padding: 2px;">BA Black anodized</td></tr> </table>	HOUSING COLOR		AA Aluminium anodized (Standard)	BA Black anodized	<table style="width: 100%; border-collapse: collapse;"> <tr><th colspan="2" style="text-align: left; padding: 2px;">LEADERCABLE LENGTH</th></tr> <tr><td style="padding: 2px;">ETE End to end - wiring</td></tr> <tr><td style="padding: 2px;">003 + 30 cm (ca. 1 ft)</td></tr> <tr><td style="padding: 2px;">006 + 60 cm (ca. 2 ft)</td></tr> <tr><td style="padding: 2px;">009 + 90 cm (ca. 3 ft)</td></tr> <tr><td style="padding: 2px;">012 + 1,2 m (ca. 4 ft)</td></tr> </table>	LEADERCABLE LENGTH		ETE End to end - wiring	003 + 30 cm (ca. 1 ft)	006 + 60 cm (ca. 2 ft)	009 + 90 cm (ca. 3 ft)	012 + 1,2 m (ca. 4 ft)	<table style="width: 100%; border-collapse: collapse;"> <tr><th colspan="2" style="text-align: left; padding: 2px;">GLARE PROTECTION</th></tr> <tr><td style="padding: 2px;">OP No glare protection</td></tr> <tr><td style="padding: 2px;">HL Hex louver (internal)</td></tr> <tr><td style="padding: 2px;">LLO Linear louver (internal)</td></tr> </table>	GLARE PROTECTION		OP No glare protection	HL Hex louver (internal)	LLO Linear louver (internal)	<table style="width: 100%; border-collapse: collapse;"> <tr><th colspan="2" style="text-align: left; padding: 2px;">MOUNTING OPTION</th></tr> <tr><td style="padding: 2px;">MPA Mounting Plate Basic</td></tr> <tr><td style="padding: 2px;">MSH Mounting Set Hinge</td></tr> </table>	MOUNTING OPTION		MPA Mounting Plate Basic	MSH Mounting Set Hinge
TYP - LUMINOUS COLOR																														
PW22 pureWhite - 2200 K																														
PW27 pureWhite - 2700 K																														
PW30 pureWhite - 3000 K																														
PW40 pureWhite - 4000 K																														
HOUSING COLOR																														
AA Aluminium anodized (Standard)																														
BA Black anodized																														
LEADERCABLE LENGTH																														
ETE End to end - wiring																														
003 + 30 cm (ca. 1 ft)																														
006 + 60 cm (ca. 2 ft)																														
009 + 90 cm (ca. 3 ft)																														
012 + 1,2 m (ca. 4 ft)																														
GLARE PROTECTION																														
OP No glare protection																														
HL Hex louver (internal)																														
LLO Linear louver (internal)																														
MOUNTING OPTION																														
MPA Mounting Plate Basic																														
MSH Mounting Set Hinge																														
<table style="width: 100%; border-collapse: collapse;"> <tr><th colspan="2" style="text-align: left; padding: 2px;">BEAM ANGLE</th></tr> <tr><td style="padding: 2px;">8X8 8° x 8°</td></tr> <tr><td style="padding: 2px;">10X10 10° x 10°</td></tr> <tr><td style="padding: 2px;">23X23 23° x 23°</td></tr> <tr><td style="padding: 2px;">43X43 43° x 43°</td></tr> <tr><td style="padding: 2px;">52X52 52° x 52°</td></tr> <tr><td style="padding: 2px;">8X31 8° x 31°</td></tr> <tr><td style="padding: 2px;">10X42 10° x 42°</td></tr> <tr><td style="padding: 2px;">12X60 12° x 60°</td></tr> <tr><td style="padding: 2px;">14X100 14° x 100°</td></tr> <tr><td style="padding: 2px;">30X60 30° x 60°</td></tr> <tr><td style="padding: 2px;">20X60Y10R 20° x 60° (Tilt in C0-plane: 10°)</td></tr> <tr><td style="padding: 2px;">20X60Y10L 20° x 60° (Tilt in C0-plane: -10°)</td></tr> </table>	BEAM ANGLE		8X8 8° x 8°	10X10 10° x 10°	23X23 23° x 23°	43X43 43° x 43°	52X52 52° x 52°	8X31 8° x 31°	10X42 10° x 42°	12X60 12° x 60°	14X100 14° x 100°	30X60 30° x 60°	20X60Y10R 20° x 60° (Tilt in C0-plane: 10°)	20X60Y10L 20° x 60° (Tilt in C0-plane: -10°)																
BEAM ANGLE																														
8X8 8° x 8°																														
10X10 10° x 10°																														
23X23 23° x 23°																														
43X43 43° x 43°																														
52X52 52° x 52°																														
8X31 8° x 31°																														
10X42 10° x 42°																														
12X60 12° x 60°																														
14X100 14° x 100°																														
30X60 30° x 60°																														
20X60Y10R 20° x 60° (Tilt in C0-plane: 10°)																														
20X60Y10L 20° x 60° (Tilt in C0-plane: -10°)																														

Sample Order Code: linea-m-hp-in-pW30-ndim-3/922-23x23-AA-Y01

* Project-specific options are available - Please contact our Sales Representative for further information.