



linea xs eco

tunableWhite

SPECIFICATION SHEET

BION TECHNOLOGIES GMBH

Lindberghstrasse 15
86343 Koenigsbrunn

Tel: +49 (0)8231/95787-0
Fax: +49 (0)8231/95787-29

www.biontechnologies.com
info@biontechnologies.com

YouTube: <http://www.youtube.com/BIONTECHNOLOGIES>

© 2016, BION TECHNOLOGIS GMBH
All rights reserved / Subject to change / Specifications may change without notice.

| | | |
|----------------|-----------------|-------------|
| Project | Fixture# | Date |
| | | Firm |



Ordering Information

Choose the option that suits your needs and write its corresponding code on the appropriate line to form the product code.

LIN-XS-ECO- TW2240 - DIMMING - FIXTURE LENGTH - BEAM ANGLE - HOUSING COLOR - GLARE PROTECTION - WIRING CONFIGURATION - LEADERCABLE LENGTH - MOUNTING OPTION - Y01

| TYP - LUMINOUS COLOR | | DIMMING | | FIXTURE LENGTH | | BEAM ANGLE | | HOUSING COLOR | | GLARE PROTECTION | | WIRING CONFIGURATION | | LEADERCABLE LENGTH | | MOUNTING OPTION | |
|--|--|--|--|---|--|---|--|---|--|---|--|--|--|--|--|---|--|
| TYP - LUMINOUS COLOR TW2240 tunableWhite - 2200 K - 4000 K | | DIMMING DALI Dimmable - DALI DMX Dimmable - DMX | | FIXTURE LENGTH 324 324 mm / 12.76 in 477 477 mm / 18.78 in 629 629 mm / 24.76 in 782 782 mm / 30.79 in 934 934 mm / 36.77 in 1087 1087 mm / 42.8 in 1239 1239 mm / 48.78 in | | BEAM ANGLE 8X8 8° x 8° 10X10 10° x 10° 23X23 23° x 23° 43X43 43° x 43° 8X31 8° x 31° 10X42 10° x 42° 12X60 12° x 60° 14X100 14° x 100° 30X60 30° x 60° 60X30 60° x 30° | | HOUSING COLOR AA Aluminium anodized (Standard) BA Black anodized | | GLARE PROTECTION OP No glare protection HL Hex louver (internal) LLO Linear louver (internal) | | WIRING CONFIGURATION IOCC IN/OUT with Connector IXCX only IN with Connector IOOC IN open end / OUT socket IOOO IN/OUT with open ends IXOX only IN with open ends | | LEADERCABLE LENGTH ETE End to end - wiring 003 + 30 cm (ca. 1 ft) 006 + 60 cm (ca. 2 ft) 009 + 90 cm (ca. 3 ft) 012 + 1,2 m (ca. 4 ft) | | MOUNTING OPTION ND without bracket BS Universal mounting bracket | |

* Project-specific options are available - Please contact our Sales Representative for further information.